

TECHNICAL DATASHEET

FURNITURE OIL (MÖBELOLJA)

Selder & Company AB 18.3.2021

www.selder.com/en

Drying oil for impregnating joinery in oak, ash, tropical hardwood and similar. Contains no solvents. Use PRIMER OIL for other species of wood and LINSEED VARNISH OIL for polishing.



FURNITURE OIL is linseed oil from which the non-drying ingredients have been removed with our unique refining method. It penetrates the substrate and dries quickly by a reaction with the oxygen in the air to linoxyn, a natural polymer with excellent adhesion. It is non-biodegradable, water-repellent and resistant to fats, petroleum products, salts and household acids.

Work manual

Visit our website at www.selder.com/en and follow its detailed instructions.

Instructions – summary

Impregnate: Sand the workpiece with an at least #180 abrasive net. A coarser abrasive leaves marks that the oil cannot fill as it acts inside the wood. Heat FURNITURE OIL to 130 °C, preferably in a deep fryer. Apply liberally with a natural bristle brush. Spread

from places that are saturated to places that still absorb oil. Apply and spread until the entire surface is saturated.

Sand in the oil that remains on the surface with an abrasive net, first with #120, then with #320. The oil-saturated sanding dust fills the small irregularities of the wood surface, making it even and smooth.

Wipe off: After about 20 minutes, thoroughly wipe off any oil and all sanding dust remaining on the surface, otherwise it forms a sticky skin.

Wash brushes, tools and utensils with strong soft soap.

Allow time to oxidize for at least 24 hours.

For a glossy surface, polish the oxidized oil sanded surface with LINSEED VARNISH OIL. See the work manual.

Worker protection: Respiratory protection is not required. Provide good ventilation, especially when working with oil at 130 °C. The oil has low thermal conductivity and at this temperature does not cause burns in the event of spillage.

Contains: Drying (oxidizing) fatty acids of linseed oil.

Dry matter: 100 %

Drying time: Less than 24 hours at 20 °C and good ventilation.

Consumption: 1-2 dl/m².

Packaging: 1 and 5 litre cans, 200 litre drums, 1000 litre IBC containers.

Safety: Consists of oxidizing fatty acids that **can ignite spontaneously**. Cloths, shavings and other porous materials that have been moistened with FURNITURE OIL must be immersed in water without delay.

Unfit for consumption: Dries in the digestive tract and causes diarrhea.

Metal objects burn when lifted from hot oil.

Selder & Company AB
Knivstagatan 11
75323 Uppsala,
Sweden
+46 73 0700 384

