

TECHNICAL DATASHEET

STRONG SOFT SOAP (GROVSÅPA)

Selder & Company AB 1.2.2021

www.selder.com/en

A strong linseed oil soap that dissolves all fats.



Work manual

Very heavy dirt; engines and the like: Brush the surface with STRONG SOFT SOAP. Work with a dish brush. Rinse the surface with water when the dirt has dissolved.

Repeat if necessary.

Heavy dirt: Dilute STRONG SOFT SOAP with about half water or until it can be sprayed with a hand sprayer. Spray the dirty surface abundantly. Work the dirt and rinse.

Light dirt: Dilute STRONG SOFT SOAP down to 1/100 and apply. Let work and scrub with a brush or wash off with a high-pressure washer.

Brushes with residues of linseed oil or linseed oil paint: Cover the brush with STRONG SOFT SOAP and knead it. The soap becomes thin liquid and/or coloured when it dissolves paint. Rinse with water. Then squeeze the water out of the brush, cover again with soap and knead. Repeat until the soap no longer becomes thin and/or coloured.

Rinse the brush repeatedly and thoroughly with water. Allow the brush to dry thoroughly before using it with Selder's paints or oils.

Dried residues of linseed oil or linseed oil paint: Soak the item in undiluted STRONG SOFT SOAP until the dirt has softened and can be removed. This may take several days.

NOTE: STRONG SOFT SOAP dissolves linseed oil paint and attacks aluminium.

Worker safety: Wear gloves when working with STRONG SOFT SOAP, as it dries out the skin. Protect your eyes, as the soap is a potent irritant.

Visit our website at www.selder.com/en for more information.

Contains: Linseed oil soap 50 % vol., water 50 % vol.

Packaging: 1 and 5 litre cans.

Selder & Company AB
Knivstagatan 11
75323 Uppsala, Sweden
atle@selder.com
+46 73 0700 384

